

Specification Sheet

Foamstream — M600 —

The Foamstream M600 is a smaller, more compact and more lightweight design than the M1200 – suitable to mount on a range of vehicles including a variety of UTVs. With a flow rate of 1.85 gallons per minute, the M600 is particularly well-suited to smaller-scale jobs and harder to reach areas in inner-city and rural environments. Powered by propane to help reduce noise and carbon emissions. It also includes additional functionality for sanitization, street cleaning, gum removal and power washing.



MACHINE MEASUREMENTS	
HEIGHT	3' 11-1/4"
WIDTH	3' 3-1/2"
WIDTH + INTEGRATED TANK	4' 1-2/3"
DEPTH	2' 7-1/2"
DEPTH + INTEGRATED TANK	3' 7-3/4"
WEIGHT DRY UNIT	529 lb.
WEIGHT WET UNIT	595 lb.
GENERATOR	LPG powered 230V 60 Hz pure sine wave inverter generator
EMISSIONS CLASS	EPA/CARB compliant
BOILER	164,000 BTU diesel powered, 230V 60 Hz with dual-stage pump, 2900 psi 1/2" stainless steel coil.
BOILER EFFICIENCY	93%
WAND WEIGHT	5.5 lb.
HOSE LENGTH	98 ft.
OPERATING MEASUREMENTS	
INTERNAL OPERATING TEMPERATURE	208 °F
OPERATING TEMPERATURE AT WAND	208 °F
OVER-TEMPERATURE CUTOUT	248 °F
WEED CONTROL WAND PRESSURE	15 psi (atmospheric)
CLEANING WAND PRESSURE	290 - 363 psi
FLOW RATE AT WAND (per minute)	1.85 gal.
OPERATING NOISE LEVEL AT 1 m	< 77 dB
OPERATING NOISE LEVEL AT 5 m	< 68 dB
CONSUMABLE MEASUREMENTS	
PROPANE TANK CAPACITY	Subject to availability
DIESEL TANK CAPACITY	9.25 gal.
GENERATOR / PUMP OIL	SAE 5W40
GENERATOR OIL CAPACITY	20 oz.
PUMP OIL CAPACITY	10 oz.
WATER TANK CAPACITY	71 gal.
FOAM TANK CAPACITY	4 gal.
FOAM JUG - GROSS WEIGHT	57 lb.
FOAM CAPACITY WEIGHT	55 lb.
FOAM STORAGE TEMP. REQUIRED	41-104 °F
OUTPUT PER HOUR : 100% COVERAGE	
LOW VEGETATION DENSITY	4521 sq. ft.
HIGH VEGETATION DENSITY	3014 sq. ft.
TIME TAKEN TO TREAT 1 ha (HOURS)	< 24

