

Specification Sheet

Foamstream — M600 —

The Foamstream M600 is a smaller, more compact and more lightweight design than the M1200 – suitable to mount on a range of vehicles including a variety of UTVs. With a flow rate of 7 litres per minute, the M600 is particularly well-suited to smaller-scale jobs and harder to reach areas in inner-city and rural environments. Powered by propane to help reduce noise and carbon emissions. It also includes additional functionality for sanitisation, street cleaning, gum removal and power washing.



MACHINE MEASUREMENTS	
HEIGHT	1200 mm
WIDTH	1000 mm
WIDTH + INTEGRATED TANK	1260 mm
DEPTH	800 mm
DEPTH + INTEGRATED TANK	1110 mm
WEIGHT DRY UNIT	240 kg
WEIGHT WET UNIT	270 kg
GENERATOR	LPG powered 230V 50 Hz pure sine wave inverter generator
EMISSIONS CLASS	EU emissions compliant
BOILER	48 kWh diesel powered, 230V 50 Hz with dual-stage pump, 200 bar 1/2" stainless steel coil
BOILER EFFICIENCY	93%
LANCE WEIGHT	2.5 kg
HOSE LENGTH	30 m
OPERATING MEASUREMENTS	
INTERNAL OPERATING TEMPERATURE	98 °C
OPERATING TEMPERATURE AT LANCE	98 °C
OVER-TEMPERATURE CUTOUT	120 °C
WEED CONTROL LANCE PRESSURE	1 bar (atmospheric)
CLEANING LANCE PRESSURE	20 – 25 bar
FLOW RATE AT LANCE (per minute)	7 L
OPERATING NOISE LEVEL AT 1 m	< 77 dB
OPERATING NOISE LEVEL AT 5 m	< 68 dB
CONSUMABLE MEASUREMENTS	
PROPANE TANK CAPACITY	Optional
DIESEL TANK CAPACITY	35 L
GENERATOR / PUMP OIL	SAE 5W40
GENERATOR OIL CAPACITY	0.6 L
PUMP OIL CAPACITY	0.3 L
WATER TANK CAPACITY	270 L
FOAM TANK CAPACITY	15 L
FOAM JUG – GROSS WEIGHT	26 kg
FOAM CAPACITY WEIGHT	25 kg
FOAM STORAGE TEMP. REQUIRED	5-40 °C
OUTPUT PER HOUR : 100% COVERAGE	
LOW VEGETATION DENSITY	420 m ²
HIGH VEGETATION DENSITY	280 m ²
TIME TAKEN TO TREAT 1 ACRE (HOURS)	< 10

